

Vorschweisssflansche DIN2635 PN40													
DN	d1	D	b	k	h1	d3	s	h2	d4	f	d2	Löcher	kg
10	14.0	90	16	60	35	25	1.8	6	40	2	14	4	0.661
10	17.2	90	16	60	35	28	1.8	6	40	2	14	4	0.661
15	20.0	95	16	65	38	30	2.0	6	45	2	14	4	0.746
15	21.3	95	16	65	38	32	2.0	6	45	2	14	4	0.746
20	25.0	105	18	75	40	38	2.3	6	58	2	14	4	1.060
20	26.9	105	18	75	40	40	2.3	6	58	2	14	4	1.060
25	30.0	115	18	85	40	42	2.6	6	68	2	14	4	1.290
25	33.7	115	18	85	40	46	2.6	6	68	2	14	4	1.290
32	38.0	140	18	100	42	52	2.6	6	78	2	18	4	1.880
32	42.4	140	18	100	42	56	2.6	6	78	2	18	4	1.880
40	44.5	150	18	110	45	60	2.6	7	88	3	18	4	2.330
40	48.3	150	18	110	45	64	2.6	7	88	3	18	4	2.330
50	57.0	165	20	125	48	72	2.9	8	102	3	18	4	2.820
50	60.3	165	20	125	48	75	2.9	8	102	3	18	4	2.820
65	76.1	185	22	145	52	90	2.9	10	122	3	18	8	3.740
80	88.9	200	24	160	58	105	3.2	12	138	3	18	8	4.750
100	108.0	235	24	190	65	128	3.6	12	162	3	22	8	6.520
100	114.3	235	24	190	65	134	3.6	12	162	3	22	8	6.520
125	133.0	270	26	220	68	155	4.0	12	188	3	26	8	9.070
125	139.7	270	26	220	68	162	4.0	12	188	3	26	8	9.070
150	159.0	300	28	250	75	182	4.5	12	218	3	26	8	11.800
150	168.3	300	28	250	75	192	4.5	12	218	3	26	8	11.800
175	193.7	350	32	295	82	218	5.6	15	260	3	30	12	18.200
200	219.1	375	34	320	88	244	6.3	16	285	3	30	12	21.500
250	267.0	450	38	385	105	298	7.1	18	345	3	33	12	34.900
250	273.0	450	38	385	105	306	7.1	18	345	3	33	12	34.900
300	323.9	515	42	450	115	362	8.0	18	410	4	33	16	49.700
350	355.6	580	46	510	125	408	8.8	20	465	4	36	16	68.100
350	368.0	580	46	510	125	408	8.8	20	465	4	36	16	68.100
400	406.4	660	50	585	135	462	11.0	20	535	4	39	16	96.500
400	419.0	660	50	585	135	462	11.0	20	535	4	39	16	96.500
500	508.0	755	52	670	140	562	14.2	20	615	4	42	20	117.000